

# WEBA TECHNOLOGY

## Antifreeze Additive Packages

WEBA Technology Corp. makes inhibitor systems for blending glycol and water to make antifreeze/coolants that cover most industry and OEM specifications. Our additive packages allow the finished fluid manufacturer to make everything from automotive light-duty to heavy-duty diesel antifreezes, both conventional and extended life. Our formulations include traditional conventional light and heavy duty, Hybrid Organic Acid Technology (HOAT), NOAT and OAT (Organic acid technology), Poly-organic Acid Technology (POAT) and Multi-Functional Organic Acid Technology for both light and heavy-duty applications. Our series of OAT inhibitors are the latest technology for making long-lasting coolants. The METALGUARD® antifreeze additive packages provide proven corrosion prevention, fluid longevity and ease of blending. WEBA Technology's comprehensive technical expertise and customer support services will assist with problems, the pursuit of new business and new product development.

### METALGUARD A85 is Formulated to meet the following Specifications

- ASTM D 3306
- ASTM D 4985
- ASTM D 6210/11
- TMC of ATA RP329/330/338

Nearly all of OEM automotive light-duty and heavy-duty specifications are patterned after or identical to the ASTM standard specifications given above. For individual OEM specification compliance contact your sales representative. Note that the ASTM specifications listed include the key performance tests (ASTM D1384, D4340, D1881, D2570, D2809).

### Technical Support

WEBA Technology can answer questions about ASTM standards and industry specifications as well as help with many other questions relating to antifreeze and glycols. To confirm that your finished product meets the required industry specifications, WEBA's laboratory can help you with problem solving and testing associated with any products containing our inhibitor package.

### Quality Control

WEBA Technology's additive packages must pass all our quality control tests prior to shipment. They are tested for conformance with product specifications and industry standards. Certificate of analysis are provided with every shipment. Complete ASTM performance tests are available by request.

## METALGUARD® A85

Multi-Functional Organic Acid Technology for Light and Heavy-Duty Use  
Extended Life Additive Package for use with Ethylene or Propylene Glycol

### Description and Applications

METALGUARD A85 is a new-generation additive developed specifically to make an extended life antifreeze/coolant with superior performance and durability under the more demanding conditions of higher combustion temperatures and cylinder pressures of today's low emission heavy-duty engines. It can be used in all types of heavy-duty engines, and is excellent for light-duty and automotive service, as well.

As an all-organic formulation, METALGUARD A85 does not contain any conventional inorganic salts (free of nitrite, nitrate, silicate, phosphate and borate), amines or 2-ethylhexanoic acid. It employs advanced multi-functional organic acid technology that combines three types of corrosion protection in one molecule, and uses this in combination with other organic di-acids and azoles. This new type of additive/corrosion inhibitor system minimizes deposit formation, protects all types of metal, has high compatibility with non-metal components (plastics and elastomers), provides outstanding cylinder liner cavitation/pitting protection, and is compatible with all types of coolant technologies. METALGUARD A85's performance is further enhanced with anti-scalant, anti-fouling, and water pump lubrication additives.

Antifreeze/coolant made with METALGUARD A85 meets ASTM D6210, the specification for fully-formulated, heavy-duty applications without the use of SCA's or extenders. It provides cooling system protection for 600,000 on-road miles, or longer. In off-road and stationary engines, it provides protection for 12,000 hours or 6 years, whichever comes first. Longer service life is possible with a strong coolant maintenance program. If required, a concentrated booster is available for restoring the inhibitor content when coolant loss has been made-up with water or to extend the coolant service life beyond the standard miles/hours.

It is recommended that antifreeze/coolant made with METALGUARD A85 be inspected at a 90-day interval to detect any obvious contamination, phase separation, cloudiness, precipitation or significant pH change. A full analysis of coolant made with METALGUARD A85 is recommended at least every 300,000 miles, or when visual and pH checks indicate a problem.

### Typical Product Specifications

Specifications below are tested using virgin glycols.

#### As concentrated METALGUARD A85 inhibitor package:

Visual	Clear-cloudy, yellow to amber liquid
Specific Gravity; 70°F/21°C	1.138-1.148
pH	9.0-9.5

#### As concentrated Antifreeze Ethylene Glycol Propylene Glycol

Specific Gravity; 70°F	1.117 min.	1.045 min.
pH; 50%	8.0-8.5	8.0-8.5
Freeze Point; 50%	-34°F (-36°C) max.	-28°F (-33°C) max.
Reserve Alkalinity	6.5 min.	6.5 min.

# METALGUARD® A85

## Blending and Use Instructions

METALGUARD A85 should be blended with glycols meeting ASTM E1177 EG-1, EG-2, PG-1 or PG-2 requirements. Dilution water should be deionized or at least meet the limits given in Table X1.1 in the appendix of ASTM D6210 standard.

**Blending:** Upon opening the drum, stir thoroughly. If you use only a portion of the drum (i.e. a few gallons at a time) you need to thoroughly mix the drum of additive prior to pulling out the required amount. If you use the entire drum to make a bulk blend you do not need to mix the drum prior to use.

**To make antifreeze concentrate:** First charge the desired quantity of glycol to the blending tank. Heat the glycol to 50°F (10°C) or higher, and adjust its pH range to a range of 7.0-9.5, if necessary. Maintain this temperature throughout the blending procedure. Based on the quantity of glycol being treated, add 8.0% by volume of the additive package while agitating or circulating glycol. Use 7.27 x 55-gallon drums (400 gallons) per 5,000 gallons (1514 liters per 18,925 liters of glycol). Good agitation is vital to making a consistent and proper product. Continue to agitate for 30-60 minutes after all of the additive package has been transferred into the blending vessel.

**To make 50/50 (50% glycol/50% water):** Follow glycol instructions in concentrate section above, and then add 4.0% by volume of the additive package using the previous instructions. Use 3.64 x 55 gallon drum (200 gallons) per 5,000 gallons (757 liters per 18,925 liters) of 50% glycol/50% water mixture.

**Antifoam:** Add the appropriate amount of antifoam to allow your product to pass a foam test. For reclaimed glycol antifreeze concentrate use 1.5 gallons (5.68L) per 5000 gallons (18,925L) of antifreeze concentrate (0.75 gallons/2.84L in 50/50). More may be needed depending upon glycol-base quality. For virgin glycols use 1.0 gallons (3.79L) per 5000 gallons (18,925L) of antifreeze concentrate (0.5 gallons/1.89L in 50/50). Antifoam may be purchased in 5-gallon (18.93L) pails from WEBA Technology.

**Dye:** As the last step add the color of dye that you wish to use. If you need help determining dye colors or use rates you may contact us. We can help you to select the proper color for the antifreeze you wish to make. Dye can be ordered from WEBA Technology or from the dye company of your choice. We recommend and use dyes from Robert Koch Industries <http://www.kochcolor.com>.

**Testing:** Test your finished product to be sure it conforms to specifications. See below paragraph on quality control.

**Storage:** METALGUARD A85 should be stored at 50°F or higher; periods of up to several hours at temperatures down to 35-40°F can be tolerated. If a container arrives very cold to your warehouse, immediately place it in a hot room for 1-2 days then stir thoroughly prior to use. Once a container is opened there is a possibility of some evaporation of the water base, so close the container tightly after each use. High temperatures, above 90°F (32°C), for an extended period of time may also cause degradation of the inhibitors. If you are in an area of the country with continuous high heat store the additive in a cooler area of your warehouse.

**Water Quality And Dilution:** When antifreeze concentrate is diluted to 50% by volume with water, the water of dilution must be of acceptable quality. Dilution water should be deionized or at least meet the limits given in Table X1.1 in the appendix of ASTM D6210 standard. Higher hardness levels may cause excessive inhibitor consumption, scale deposits and metal pitting.

**Quality Control Procedures:** WEBA Technology strongly recommends that all antifreeze producers have an internal, complete quality control program in place for manufacturing and testing of all products made for sale. Visit the Customer Information Area at <http://www.webacorp.com> for forms and more information on how to set-up a basic quality control program for your company.

# METALGUARD® A85

## Making Claims for Antifreeze/Coolant Blended with WEBA Technology's Additive Packages

The specifications listed in this bulletin are based on antifreeze produced with WEBA Technology's additive packages, virgin glycol and deionized water. Antifreeze blenders must demonstrate independent compliance with ASTM or other specifications with their antifreeze/coolant, because proper blending and quality of the glycol/water used is as important as the additive package. Note that OEM's have placed limits on the percentage of recycled glycol that can be used in factory fills as have other purchasers of antifreeze. Glycol quality specifications have also been established. Obtain copies of the specifications that you wish to meet, thoroughly read them and conduct any required tests, prior to stating that your antifreeze produced meets the specifications. WEBA Technology can provide assistance locating the necessary specifications/standards. To confirm that your finished products meet the required industry specifications, WEBA Technology recommends that you test your glycol and finished products at an accredited laboratory. Glycol should be tested for conformance with ASTM E1177 and/or ASTM D7713, and finished products should be tested for the ASTM performance tests listed on this product bulletin. Additionally, if you are using a process other than distillation for recycling your glycol tests should use the ASTM D6471/D6472 standards to determine the quality of your product. WEBA Technology can assist your company in preparing your samples for testing with pre-tests performed at the accredited laboratory. WEBA Technology will warrant our additive packages only if these procedures and the recommended blending and storage procedures are properly followed. In addition, the glycol or other base fluid used with our additive systems must meet industry or ASTM standards unless specifically exempted in our literature.

## Technical Contact Information

**WEBA Technology**  
1213 N. Sherman Ave. #351  
Madison, WI 53704 USA  
Tel: 608-819-8806  
Fax: 608-237-2054  
www.webacorp.com  
info@webacorp.com

Version date: October 12, 2015  
Supersedes: March 25, 2015  
**METALGUARD** is a registered trademark  
and may only be used with permission.