

# SAFETY DATA SHEET

Product Name: **METALGUARD A65-EXT**

SDS No.: 602

Issue Date: 3/2/2015

Version No.: 3

## SECTION 1: COMPANY AND PRODUCT IDENTIFICATION

**Product Name:** METALGUARD A65-EXT  
*Antifreeze/Coolant Extender-Booster*  
(To be used with METALGUARD A65 antifreeze/coolant, SCA precharged)

**Company Name:** WEBA Technology Corp.  
1213 N. Sherman Ave #351  
Madison, WI 53704 USA

**For More Information Call:** Tel: 608-819-8806  
Fax: 608-237-2054  
msds@webacorp.com  
SDS on-line: www.webacorp.com

**In Case of Emergency Call:** CHEMTREC - 800-424-9300 or 703-527-3887 (24 Hours/Day,  
7 Days/Week)

## SECTION 2: HAZARDOUS IDENTIFICATION

**OSHA Hazards:** Corrosive**Target Organs:** Liver**Signal Words:** Danger**Pictograms:****GHS Classification:**

Skin corrosion	Category 1B
Serious eye damage	Category 1

**GHS Label Elements, including precautionary statements:****Hazard Statements:**

H314	Causes severe skin burns and eye damage.
------	--

**Precautionary Statements:**

P260	Do not breathe dusts or mists.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do not induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local regulations.

**Potential Health Effects**

Eyes	Causes severe eye burns.
Inhalation	May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.
Skin	May be harmful if absorbed through skin. Causes skin burns.
Ingestion	May be harmful if swallowed.

**NFPA Ratings**

Health	3
Flammability	0
Reactivity	0
Specific hazard	N/A

**HMIS Ratings**

Health	3
Fire	0
Reactivity	0
Personal	E

0 =minimal 1= slight 2=moderate 3= serious 4= severe

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Component	Weight %	CAS #	EINECS# / ELINCS#	Formula	Molecular Weight
Sodium Nitrite	<9	7632-00-0	231-555-9	NaNO <sub>2</sub>	69.00 g/mol
Potassium Hydroxide	<1	1310-58-3	215-181-3	KOH	56.11 g/mol
Proprietary Ingredients & Inhibitors*	Balance	Proprietary	Proprietary	Proprietary	Proprietary

The exact percentage of composition has been withheld as trade secrets of WEBA Technology. This is acceptable in accordance with Paragraph (i) of 29 CFR §1910.1200.

**SECTION 4: FIRST-AID MEASURES**

Eyes	Rinse with plenty of water for at least 15 minutes and seek medical attention immediately.
Inhalation	Move casualty to fresh air and keep at rest. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.

Skin	Flush with plenty of water for at least 15 minutes while removing contaminated clothing and wash using soap. Get medical attention immediately.
Ingestion	Do Not Induce Vomiting! Never give anything by mouth to an unconscious person. If conscious, wash out mouth with water. Get medical attention immediately.

*\*All treatments should be based on observed signs and symptoms in the patient.*

## SECTION 5: FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media	Product is not flammable. Use water, fog, foam, carbon dioxide or dry chemical on fires involving this product. Use appropriate media for adjacent fire. Cool unopened containers with water.
Special protective equipment and precautions for firefighters	Do not release runoff from fire control methods to sewers or waterways. Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode. Full protective equipment including self-contained breathing apparatus should be used during a fire. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Seek medical attention.
Specific hazards arising from the chemical	Closed containers may rupture or explode due to steam pressure build-up when exposed to extreme heat. Water may be used to cool closed containers. May emit toxic fumes (nitrogen oxides, sodium oxides) under fire conditions. (See also Stability and Reactivity section).

## SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	See section 8 for recommendations on the use of personal protective equipment.
Environmental precautions	Prevent spillage from entering drains. Any release to the environment may be subject to federal/national or local reporting requirements.
Methods and materials for containment and cleaning up	Absorb spill with noncombustible absorbent material, then place in a suitable container for disposal. Clean surfaces thoroughly with water to remove residual contamination. Dispose of all waste and cleanup materials in accordance with regulations.

## SECTION 7: HANDLING AND STORAGE

### Precautions for safe handling:

See section 8 for recommendations on the use of personal protective equipment. Use with adequate ventilation. Wash thoroughly after using. Keep container closed when not in use.

### Conditions for safe storage, including any incompatibilities:

Store in cool, dry well ventilated area. Store only in containers that are resistant to alkaline solutions. Keep away from incompatible materials (see section 10 for incompatibilities).

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational exposure controls:** Contains no substances with occupational exposure limit values.

### Personal Protection

Eyes	Wear chemical safety glasses or goggles, and face shield if splashing is likely to occur.
Inhalation	Provide local exhaust, preferably mechanical. If exposure levels are excessive, use an approved respirator.
Skin	Wear nitrile or rubber gloves. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Other	Not Available

### Other Recommendations

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. Avoid contact with skin, eyes and clothing. Do not take internally. Clean up spills immediately. Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.)	Clear, yellow liquid.
Odor	Light chemical odor.
Odor threshold	Not Available
pH	11.5-12.5
Melting point/freezing point	Not Available
Initial boiling point and boiling range	>100 °C (>212 °F)
Flash point	Not Flammable
Evaporation rate	Not Available
Flammability (solid, gas)	Not Flammable
Upper/lower flammability or explosive limit	Not Explosive
Vapor pressure	10 mmHg at 20 °C (68 °F)
Vapor density	>2.0 (air = 1)
Specific gravity	1.110-1.130 (water = 1)
Solubility (ies)	Completely soluble in water.
Partition coefficient: n-octanol/water	Not Available
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Percent volatile by Volume	NIL

## SECTION 10: STABILITY AND REACTIVITY

Chemical Stability	Stable.
Possibility of Hazardous Reactions	Will not occur.
Conditions to Avoid	Storage below 15.5 °C (60 °F) or above 65.5 °C (150 °F)
Incompatible Materials	Strong acids, oxidizers.
Hazardous Decomposition Products	Oxides of sodium and nitrogen.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Acute Toxicity

#### Sodium Nitrite

Skin	Not Available
Eyes	Not Available
Respiratory	Not Available
Ingestion	LD50 Oral - rat - 1,267 mg/kg LD50 Oral - rabbit - 2,680 mg/kg LDLO Oral - Child - 22.5 mg/kg
Other	LD50 Intravenous - mouse - 175 mg/kg

#### Potassium Hydroxide

Skin	Not Available
Eyes	Not Available
Respiratory	Not Available
Ingestion	LD50 - Rat - 273 mg/kg

### Carcinogenicity

IARC	No components of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
NTP	No components of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA	No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

### Signs & Symptoms of Exposure

Skin	May cause irritation.
Eyes	Severe eye irritation, watering eyes, redness.
Respiratory	Depending on the concentration and duration of exposure, may cause respiratory tract irritation, a burning sensation, shortness of breath. Vapor/fumes are not generated at significant levels until temperature is elevated.
Ingestion	Burns and tissue perforation of mucous membranes of the mouth, throat, esophagus and stomach.

Chronic Toxicity	Sodium nitrite can cause cyanosis, headache, dizziness, nausea and methemoglobinemia.
Teratogenicity	Not Available
Mutagenicity	Not Available
Embryotoxicity	Not Available
Specific Target Organ Toxicity	Not Available
Reproductive Toxicity	Not Available
Respiratory/Skin Sensitization	Not Available

---

## SECTION 12: ECOLOGICAL INFORMATION

---

### Ecotoxicity

#### Sodium Nitrite

Aquatic Vertebrate	LC50 - Gambusia affinis (Mosquito fish) - 6,650 mg/l - 96 h
Aquatic Invertebrate	EC50 - Daphnia magna (Water flea) - 6,000 mg/l - 24 h
Terrestrial	Not Available

#### Potassium Hydroxide

Aquatic Vertebrate	Not Available
Aquatic Invertebrate	Not Available
Terrestrial	Not Available

Persistence and Degradability	Biodegradable.
Bioaccumulative Potential	Not Available
Mobility in Soil	Not Available
PBT and vPvB Assessment	Not Available
Other Adverse Effects	Not Available

---

## SECTION 13: DISPOSAL CONSIDERATIONS

---

Waste Residues	Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary before disposing of waste product or residues.
Product Containers	Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary before disposing of waste product container.

The information offered in section 13 is for the product as shipped. Use and/or alterations to the product may significantly change the characteristics of the material and alter the waste classification and proper disposal methods.

---

## SECTION 14: TRANSPORTATION INFORMATION

---

US DOT	UN1760, Corrosive liquids, n.o.s., (potassium hydroxide), 8, pg II
TDG	UN1760, CORROSIVE LIQUIDS, N.O.S., (POTASSIUM HYDROXIDE), 8, PG II
IMDG	UN1760, CORROSIVE LIQUIDS, N.O.S., (POTASSIUM HYDROXIDE), 8, PG II
Marine Pollutant	No
IATA/ICAO	UN1760, Corrosive liquids, n.o.s., (potassium hydroxide), 8, pg II

---

## SECTION 15: REGULATORY INFORMATION

---

TSCA Inventory Status	All ingredients are listed on the TSCA inventory.
DSCL (EEC)	All ingredients are listed on the DSCL inventory.
California Proposition 65	Not Listed
SARA 302	Not Listed
SARA 304	Not Listed
SARA 311	Acute Health Hazard
SARA 312	Acute Health Hazard
SARA 313	Not Listed
WHMIS Canada	Class E: Corrosive material.

---

## SECTION 16: OTHER INFORMATION

---

**THIS Safety Data Sheet COVERS ALL OF THE FOLLOWING PRODUCTS:**

METALGUARD A65-EXT (NO DYE)

484800

Revision	Date
Revision 1, Version 2	02/02/2015
Revision 2, Version 3	03/02/2015

Disclaimer: THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH AND FROM SOURCES WE BELIEVE RELIABLE. BUT NO WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS IS MADE. The conditions or methods of handling, storage, use and disposal of this product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. WEBA Technology Corp. recommends that the recipient of this product read this SDS carefully and follow all procedures for handling and safety. It is the buyer/user's responsibility to ensure that the activities in handling, using and distributing this product comply with all country, federal, state and local laws. Since the conditions for use of the product are not under control of the manufacturer, it is the buyer/user's responsibility to determine the conditions necessary for the safe and proper use of this product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not apply. CONSULT WEBA TECHNOLOGY CORP FOR FURTHER INFORMATION.